

OIL WATER SEPARATORS

KCPS-2000/3000



OIL WATER SEPARATORS

| CONSTRUCTION | |
|---|--|
| Polyethylene or stainless steel tank | |
| Inlet Pipes - 50mm pressure UPVC BSP female | |
| Outlet Pipe - Water 50mm DWV UPVC V66 Socket. Oil 50mm DWV UPVC V66 Socket | |
| Sludge Hopper - 50mm UPVC incorporating 50mm PVC ball valve | |
| Tank Construction - Chemical resistant UV stabilised polyethylene thickness 5mm | |
| Lid Construction - Chemical resistant UV stabilised polyethylene thickness 5mm | |

| SPECIFICATIONS | |
|---|----------------|
| Model No. | KCPS-2000/3000 |
| Length | 1100mm |
| Width | 1100mm |
| Height | 1450mm |
| Nominal Volume - Litres | 480 |
| Approximate Weight - Free Standing (Excluding pump) | 80kg |

| PART NO. | MODEL NO. | DESCRIPTION | CAPACITY | kW | VOLTAGE | PUMP |
|----------|-------------|------------------------------|----------|------|---------|-------|
| 640102 | KCPS-2000 | KCPS-2000 Standard | 2000L/H | 0.37 | 240 | KDP32 |
| 640108 | KCPS-2000IS | KCPS-2000 Intrinsically Safe | 2000L/H | 0.37 | 415 | KDP32 |
| 640354 | KCPS-2000SS | KCPS-2000 Stainless Steel | 2000L/H | 0.37 | 240 | KDP32 |
| 640126 | KCPS-3000 | KCPS-3000 Standard | 3000L/H | 0.75 | 240 | KDP38 |
| 640132 | KCPS-3000IS | KCPS-3000 Intrinsically Safe | 3000L/H | 0.75 | 415 | KDP38 |
| 640264 | KCPS-3000SS | KCPS-3000 Stainless Steel | 3000L/H | 0.75 | 240 | KDP38 |



DIMENSIONS

KCPS-2000/3000

